GA315 & GA315FF

Electric Driven Oil-Injected Screw Compressor: GA315 & GA315FF

General Information	GA315	GA315FF
Dimensions LxWxH (mm)	3386 x 2120 x 2400	4600 x 2120 x 2400
Mass (Wet - Ready to operate) (kg)	5559	6152
Discharge Outlet	50mm Evertite 2'' Male Spud with Gasket	50mm Evertite 2'' Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	78	78

Engine	GA315	GA315FF
Main Electric Motor Power (kW)	315	315
Voltage (V)	525V	525V
Frequency (Hz)	50	50
Start Up Amps (A)	1620 A	1620 A
Full Load Running Amps @ 7-10 bar (A)	540 A	540 A
Supply Circuit Breaker (A)	600 A	600 A
Electric Supply Cabling	2 x 120mm	2 x 120mm

Performance	Capacity (Free Air Delivery)		
Working Pressure	cfm	m^3/min	l/s
Pressure up to 7,5 bar(g)	2119	59,9	1000

Other features		
Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots
Robust & Silent	Water Separator	Elektronikon Touch Display
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group
Company Reg. No. 2017/250308/07

P.O. Box 13921
Witfield 1467

Atlas Copco House,
Innes Road, Jet Park

Tel: +27 (0) 345 0700
Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .