

XRVS487



Atlas Copco Portable Oil-Injected Screw Compressor: H952



General Information

Dimensions LxWxH (mm)	5650 x 2150 x 2500
Mass (Wet - Ready to operate) (kg)	5970
Fuel Tank Capacity (l)	796
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	76

Engine

CAT C13 ACERT T3

Power (kW)	328
Fuel Consumption (100% load) (l/h)	63

Performance

With Aftercooler

	Bar	Cfm	M ³ /Min	L/s
Free Air Delivery	25	1051	29,8	496

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Forklift Slots & Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe light (Indicating Unit is operational)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-17